

Formula X-treme™

LOW-FOAMING FLOOR STRIPPER



Ideal for recovery by wet/dry vacuum or automatic scrubber;
empty reclaim tanks less frequently

SURFACES



WHY FORMULA X-TREME™ FLOOR STRIPPER:

ECONOMICAL CHOICE FOR LARGE APPLICATIONS

Powerful concentrate

5X COVERAGE RATE OF OUR CONVENTIONAL STRIPPERS

REQUIRES LESS STORAGE, MAKES LESS WASTE

EFFECTIVE STRIPPING PERFORMANCE

Butyl-based

NON-AMMONIATED

Low odor

TECHNICAL DATA

Description	Non-ammoniated, ultra high performance stripper
Appearance	Clear
Viscosity (Brookfield) @ 68°F (20°C)	<20 centipoise
Flash Point (ASTM D56-05 (2010))	>200°F (93°C)
VOC (40 CFR PART 59 SUBPART C)	60% (as supplied) 2.8% (1:20) 1.90% (1:30) 1.43% (1:40)
Fragrance	None added
Shelf Life (ASTM D1791-93 (2008))	2 years
Density (ASTM D1475 D-98 (2008))	8.2 lb/gal @ 68°F 0.98 kg/L @ 20°C



DIRECTIONS

Mix stripper per instructions for heavy, normal, or light coating removal. Apply solution liberally to the floor and allow to soak — do not allow to dry. Scrub floor with automatic scrubber or stripping machine. Rinse thoroughly with clean water and allow floor to dry before applying finish.

Read all directions and Safety Data Sheet (SDS) before using.
Directions and SDS are available for download at pioneereclipse.com

Product Code	549FS	549FSE	549Q12	549MP	549MPE
Volume	2.50 US gallons	10 liters	32 US ounces	1.06 US gallons	4 liters
Shipping Package	2 x 2.5 gallons	2 x 10 liters	12 x 32 ounces	4 x 1.06 gallons	4 x 4 liters
Pallet Quantity	48	48	44	48	48