

TimberClean™ Deep Scrub



An industrial grade cleaner formulated to remove embedded dirt and tough residual films.

WHY TIMBERCLEAN DEEP SCRUB:

BUTYL AND ALCOHOL BASED FORMULA

Breaks down residual film formations

CLEANS AGGRESSIVELY

Removes embedded dirt

DRIES QUICKLY TO PREVENT WATER DAMAGE

TECHNICAL DATA

Description	Water-based wood floor cleaner
Appearance	Yellow liquid
pH ASTM E70-07	11
Viscosity (Brookfield)	<10 centipoise
VOC 40 CFR Part 59 Subpart D	14.5% (as supplied) 2.86% (1:4)
Fragrance	No fragrance added/ alcohol (IPA)
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-13 (2008)	8.3 lb/gal

SURFACES

WOOD FLOORS

Product Code	714GL3PE
Volume	1 US Gallon
Shipping Package	3 x 1 gallon
Pallet Quantity	60

714PE_PDS 02/24



DIRECTIONS

1. Prior to using TimberClean Deep Scrub, make sure the floor is free of any debris that may be attached to the floor surface, such as chewing gum, mud, or other debris. Once all debris is loose, thoroughly vacuum the floor, paying special attention to the corners.
2. Mix TimberClean Deep Scrub using a ratio of 4 parts water to 1 part cleaner.
3. Soak several clean towels in the cleaner solution and wring them until nearly dry. Rubber gloves are recommended to prevent skin irritation.
4. Wrap a towel around a push broom and tack the floor. Refold the towel using clean sides as needed. Pay special attention to the corners.
5. For areas with stubborn surface marks, use a sponge or pad center from a red or white cleaning pad and scrub the area manually until the spot is removed.
6. Rinse the floor with clean water and clean towels.
7. Clean the floor with TimberClean, making sure to follow the instructions on the TimberClean label. NOTE: TimberClean should always be used after TimberClean Deep Scrub to ensure that the floor is left clean and is free of any residue.

Auto-Scrubber Application Method:

1. When using an automatic scrubber, mix TimberClean Deep Scrub using a ratio of 14 parts water to 1 part cleaner.
2. Scrub with a red or white cleaning pad. Make sure squeegees and scrubbing pads are in good condition and proper working order. Pay special attention to the corners.
3. Flush the tank with clean water and clean the floor with a clean water rinse.
4. Mix TimberClean using a ratio of 14 parts water to 1 part cleaner and clean the floor, following the instructions on the TimberClean label.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

Product Code	714GL3PE
Volume	1 US Gallon
Shipping Package	3 x 1 gallon
Pallet Quantity	60

714PE_PDS 02/24