

# TimberGuard™ Varsity

## WOOD FLOOR COATING

A one component, water-based urethane wood floor coating specially formulated for sports floors.

**WHY TIMBERGUARD VARSITY:  
DESIGNED FOR SPORTS FLOORS**  
Single-component, water-based formula

**CLEAR AND NON-YELLOWING**  
Floors remain vibrant for years

**QUICK DRY TIME**  
3-4 hours between coats, 90% cured in 3 days

**EASY TO APPLY**  
Flows out evenly for a uniform finish

**REDUCE WASTE**  
Opened but unused product can be stored for up to a year

Read all directions and Safety Data Sheet (SDS) before using.  
Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)



## TECHNICAL DATA

Description	Water-based polyurethane coating
Appearance	Milky white liquid
Available Sheens	High Gloss
pH ASTM E70-07	7.6
Specular Gloss (60°) ASTM D1455-87 (2008)	High Gloss: >85
Viscosity (Brookfield)	<60 centipoise
Coverage Rate	500-600 ft <sup>2</sup> /gal
Dry Time	2-3 hours for first coat
VOC 40 CFR Part 59 Subpart D	<250 g/L
Non-volatile solids ASTM D2834-95 (2008)	30%
Fragrance	Characteristic
Slip Resistance ULTM410	UL Certification Pending
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-13 (2008)	8.5 lb/gal
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

SURFACES

WOOD FLOORS

Product Code	719HGFSPE	719HGPL5PE
Volume	2.50 US gallons	5 US gallon pail
Shipping Package	2 x 2.5 gallons	1 x 5 gallons
Pallet Quantity	48	36

719PE\_PDS 02/24