

# Helios H216™

### **FLOOR MAINTAINER**

Conditions and protects LVT and other low maintenance flooring. Available in High Gloss or Matte Finish.







## WHY HELIOS H216 FLOOR MAINTAINER:

### **CONDITIONS FLOORING**

Fills in scuffs and scratches

## HIGHLY RESISTANT TO SCUFF AND BLACK HEEL MARKS

Uniform appearance with or without burnishing

### NO INTENTIONALLY ADDED PFAS

Contains no fluorosurfactants

#### DIRECTIONS

Use periodically, as needed, depending on the level of foot traffic.

- 1. Clean floor thoroughly with Helios H303 Daily Neutral Cleaner diluted 1:32 (32 ml/liter or 4 oz/gallon) in cold water.
- 2. Apply 1-2 coats of maintainer with a synthetic mop or flat finish applicator. Allow floor to dry thoroughly before re-opening to traffic.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

### TECHNICAL DATA

| Description                                     | Polymer emulsion   |
|---|--|
| Appearance                                      | Milky white  |
| Specular Gloss<br>(60°)<br>ASTM D1455-87 (2008) | High gloss >80<br>Matte <35                                  |
| Viscosity<br>(Brookfield)<br>@ 68°F (20°C)      | <10 centipoise   |
| Coverage Rate                                   | 2500 to 3000 ft²/gal<br>61 to 74 m²/liter                    |
| Dry Time  | About 30 minutes   |
| Removability ASTM D1792-17                      | Good   |
| VOC<br>40 CFR Part 59 Subpart C                 | <0.1   |
| Fragrance                                       | Mild odor  |
| Slip Resistance ULTM410                         | ULTM410 Pending  |
| Shelf Life<br>ASTM D1791-93                     | 1 year   |
| Density<br>ASTM D1475-13                        | High gloss<br>8.6 lb/gal @ 68°F<br>1.03 kg/L @ 20°C<br>Matte |
|   | 8.5 lb/gal @ 68°F<br>1.02 kg/L @ 20°C                        |
| Detergent<br>Resistance<br>ASTM D3207-17        | Excellent  |
| Freeze/Thaw<br>ASTM D3209-93                    | Passes 3 cycles  |

#### DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

MeridiClean All Purpose Cleaner & Disinfectant

NeutraQuat 256 Germicidal Disinfectant

 Product Code
 216HGFS
 216HGMPE
 216MFS
 216MMPE

 Volume
 2.50 US gallons
 1.06 US gallons
 2.50 US gallons
 1.06 US gallons

 Shipping Package
 2 x 2.5 gallons
 4 x 1.06 gallons
 2 x 2.5 gallons
 4 x 1.06 gallons

 Pallet Quantity
 48
 48
 48
 48

216 PDS 5/25