

Diamond Shine™

ULTRA HIGH SPEED FLOOR COATING



A budget-friendly UHS finish that provides a wet-look shine and superior scuff resistance.

SURFACES



WHY DIAMOND SHINE:

OUR BEST BLACK HEEL MARK RESISTANCE - FEWER BURNISHINGS

Durable wax blend

ACCELERATED DRY TIME

18% Non-Volatile Solids

REPAIRABLE HIGH GLOSS SHINE

Acrylic co-polymer

TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Specular Gloss (60°) ASTM D1455-87 (2008)	>85
Viscosity (Brookfield) (@ 68°F (20°C))	<10 centipoise
Coverage Rate	2500 to 3000 ft ² /gal 61 to 74 m ² /liter
Dry Time	About 30 minutes
Buffability	Excellent
Removability ASTM D1792-06	Excellent
VOC 40 CFR Part 59 Subpart C	0.06%
Total Solids	24%
Non-Volatile Solids ASTM D2834-95 (2008)	18%
Fragrance	Slight ammoniated
Slip Resistance ULTM410	Meets requirements
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.6 lb/gal (@ 68°F) 1.03 kg/L (@ 20°C)
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

- Nova Disinfectant
- MeridiClean All Purpose Cleaner & Disinfectant
- NeutraQuat Z56 Germicidal Disinfectant
- Triton XLC Bathroom Cleaner & Disinfectant

DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com



Floor Coating and Finishing materials as to slip resistance only. 42E6

Product Code	104FS	104 MPE	104DR
Volume	2.50 US gallons	4 liters	55 US gallons
Shipping Package	2 x 2.5 gallons	4 x 4 liters	1 x 55 gallons
Pallet Quantity	48	48	4