

# Total Eclipse™

## ULTRA HIGH SPEED FLOOR COATING

Urethane-fortified UHS finish that provides superior impact and scratch resistance.



SURFACES



### WHY TOTAL ECLIPSE:

## IMPACT RESISTANT, PREVENTS CHIPPING & SCRATCHING

Urethane-fortified

## REPAIRABLE, HIGHLY BURNISHABLE

Acrylic co-polymer

### TECHNICAL DATA

<b>Description</b>	Acrylic co-polymer emulsion
<b>Appearance</b>	Milky white
<b>Specular Gloss (60°)</b> ASTM D1455-87 (2008)	>85
<b>Viscosity (Brookfield)</b> @ 68°F (20°C)	<10 centipoise
<b>Coverage Rate</b>	2500 to 3000 ft <sup>2</sup> /gal 61 to 74 m <sup>2</sup> /liter
<b>Dry Time</b>	About 30 minutes
<b>Buffability</b>	Excellent
<b>Removability</b> ASTM D1792-06	Excellent
<b>VOC</b> 40 CFR Part 59 Subpart C	0.44%
<b>Total Solids</b>	27%
<b>Non-Volatile Solids</b> ASTM D2834-95 (2008)	22%
<b>Fragrance</b>	Slight ammoniated
<b>Slip Resistance</b> ULTM410	Meets requirements
<b>Shelf Life</b> ASTM D1791-93 (2008)	1 year
<b>Density</b> ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.02 kg/L @ 20°C
<b>Detergent Resistance</b> ASTM D3207-92 (2008)	Excellent
<b>Freeze/Thaw</b> ASTM D3209-93 (2008)	Passes 3 cycles

#### DISINFECTANT COMPATIBILITY:

The following Pioneer Eclipse disinfectants are safe to use on this floor coating when correctly diluted and used according to the product directions. Bleach and other corrosives may cause damage.

- Nova Disinfectant
- MeridiClean All Purpose Cleaner & Disinfectant
- NeutraQuat 256 Germicidal Disinfectant
- Triton XLC Bathroom Cleaner & Disinfectant

### DIRECTIONS

Apply thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)



Floor Coating and Finishing materials as to slip resistance only. 42E6

<b>Product Code</b>	138FS
<b>Volume</b>	2.50 US gallons
<b>Shipping Package</b>	2 x 2.5 gallons
<b>Pallet Quantity</b>	48