

Rebound[™] Cleaner/Enhancer

CLEANER/ENHANCER



An effective one step cleaner and enhancer, **Rebound** may be applied by automatic scrubber or damp-mop. Cleans and enhances coating for a brilliant wet-look shine when burnished with UHS burnishers.

DIRECTIONS

Read all directions and Safety Data Sheet (SDS) before using.

- 1. Sweep the floor with a dust mop.
- 2. Dilute product at:
 - 1:128 (8 ml per 1 liter of water) for automatic scrubber application or 1:256 (4 ml per 1 liter of water) for mop-on application.
- 3. Scrub the floor and pick up solution in one pass or scrub with a damp mop.
- 4. Allow floor to dry thoroughly before burnishing.

SURFACES

Vinyl composition tile ("VCT"), linoleum, and most types of terrazzo, marble, concrete, quarry tile and treated wood floors.



TECHNICAL DATA

Description Water-based cleaner/enhancer

Appearance Clear green

Fragrance Lemon

pH (ASTM D1792-06) 9 - 10 Flash Point (ASTM D1792-06) >70°C

Viscosity (Brookfield) 16-25 mPa.S

Drying Time Approximately 15 minutes

 Non-volatile solids
 46%

 ASTM D2834-95 (2008)
 46%

 Slip Resistence ULTM410
 Meets requirements

 Shelf Life ASTM D1791-93 (2008)
 2 years

 Density ASTM D1475-13 (2008)
 1,03 g/cm³

 Freeze/Thaw ASTM D3209-93 (2008)
 Passes 3 cycles

VOC 0,9% (as supplied)

SDS available for download at www.pioneereclipse.com



Product Code 211L5

Volume 5 liters

Shipping Package 2 x 5 liters

Pallet Quantity 64 cases

