

Eclipse™

ANTI-SLIP TREATMENT

An indoor/outdoor anti-slip floor treatment formulated to make smooth and/or wet surfaces less slippery.



SURFACES



WHY ECLIPSE ANTI-SLIP TREATMENT:

INCREASES THE CO-EFFICIENT OF FRICTION TO REDUCE THE POTENTIAL FOR SLIPS AND FALLS

INDOOR AND OUTDOOR USE

NO CHANGE IN APPEARANCE OF SURFACE WHEN USED CORRECTLY

TECHNICAL DATA

Description	Anti-Slip / surface modifier Ready to use
Appearance	Clear colorless
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise
Flash Point ASTM D56-05 (2010)	>200°F (93°C)
Coverage Rate*	50 to 250 ft ² /gal 4 to 7 m ² /liter
Dry Time	10 - 15 minutes
VOC 40 CFR Part 59 Subpart C	0%
Fragrance	Mild odor
Shelf Life ASTM D1791-93 (2008)	2 years
Density ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.03 kg/L @ 20°C
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

DIRECTIONS

Biodegradable, suitable for indoor and outdoor use.

Read all directions and Safety Data Sheets (SDS) before using.

Detailed directions and SDS sheets are available for download at pioneereclipse.com

*Coverage is approximate and may vary depending on surface finish/texture, concrete condition, climatic conditions, etc.

Product Code	427MPE
Volume	4 liters
Shipping Package	4 x 4 liters
Pallet Quantity	48