

# Eclipse™

## CERAMIC GROUT SEALER

An indoor/outdoor grout sealer that provides a durable, non-film forming, continuous protective barrier on porous surfaces.



### WHY ECLIPSE:

RESISTS OIL AND WATER STAINS  
BETTER THAN MINERAL OIL/SILICONE  
BASED SEALERS

Water-based fluorochemical solution

RESISTS ETCHING

IMPROVES CLEANING AND  
MAINTENANCE EFFECTIVENESS

TRANSPARENT, DOES NOT CHANGE  
THE NATURAL LOOK OF THE SURFACE

Clear formula

### DIRECTIONS

Penetrating Grout Sealer is ready-to-use. Do NOT dilute.

Apply sealer with pump sprayer set to a medium spray. Follow label instructions for proper coverage. Do not apply solution so heavily that puddles are formed.

Highly porous surfaces require a second treatment which may be applied after the first treatment is dry (15-30 minutes).

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)

### TECHNICAL DATA

<b>Description</b>	Ceramic Grout Sealer
<b>Appearance</b>	Clear, straw-colored
<b>Viscosity (Brookfield)</b> @ 68°F (20°C)	<10 centipoise
<b>Flash Point</b> ASTM D56-05 (2010)	>200°F (93°C)
<b>Coverage Rate</b>	50 to 250 ft <sup>2</sup> /gal 1 to 6 m <sup>2</sup> /liter
<b>Dry Time</b>	15 - 30 minutes
<b>VOC</b> 40 CFR Part 59 Subpart D	<50 g/l
<b>pH</b> ASTM E70-07	9.6
<b>Franchise</b>	No added fragrance
<b>Shelf Life</b> ASTM D1791-93 (2008)	2 years
<b>Density</b> ASTM D1475-98 (2008)	8.4 lb/gal @ 68°F 1.01 kg/L @ 20°C
<b>Detergent Resistance</b> ASTM D3207-92 (2008)	Excellent
<b>Freeze/Thaw</b> ASTM D3209-93 (2008)	Passes 3 cycles

SURFACES



Product Code	460CMPE
Volume	4 liters
Shipping Package	4 x 4 liters
Pallet Quantity	48