

# EnviroStar™

## LOW ODOR FLOOR STRIPPER



A strong, low odor stripper certified environmentally responsible.

### WHY ENVIROSTAR LOW ODOR FLOOR STRIPPER:

#### EXTRA STRENGTH STRIPPING PERFORMANCE

Benzyl-based

#### USE IN OCCUPIED SPACES

Low Odor

#### ENVIRONMENTALLY RESPONSIBLE

Green Seal Certified

### TECHNICAL DATA

**Description** Low odor stripper

**Appearance** Clear

**Viscosity (Brookfield)** <5 centipoise  
@ 68°F (20°C)

**Flash Point** >200°F (93°C)  
ASTM D56-05 (2010)

**VOC** 9.77% (as supplied)  
40 CFR PART 59 SUBPART C 1.97% (1:4)  
1.10% (1:8)  
0.90% (1:10)

**Fragrance** None added

**Shelf Life** 2 years  
ASTM D1791-93 (2008)

**Density** 8.5 lb/gal @ 68°F  
ASTM D1475 D-98 (2008) 1.02 kg/L @ 20°C

SURFACES



### DIRECTIONS

Mix stripper per instructions for heavy, normal, or light coating removal.  
Apply solution liberally to the floor and allow to soak – do not allow to dry.  
Scrub floor with automatic scrubber or stripping machine.  
Rinse thoroughly with clean water and allow floor to dry before applying finish.

Read all directions and Safety Data Sheet (SDS) before using.  
Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)



Product Code	515FS	515MP	515MPE
Volume	2.50 US gallons	1.06 US gallons	4 liters
Shipping Package	2 x 2.5 gallons	4 x 1.06 gallons	4 x 4 liters
Pallet Quantity	48	48	48