

Formula X-treme™

FLOOR STRIPPER



An effective, super concentrated stripper.

SURFACES



WHY FORMULA X-TREME™ FLOOR STRIPPER:

ECONOMICAL CHOICE FOR LARGE APPLICATIONS

Powerful concentrate

5X COVERAGE RATE OF OUR CONVENTIONAL STRIPPERS

REQUIRES LESS STORAGE, MAKES LESS WASTE

EFFECTIVE STRIPPING PERFORMANCE

Butyl-based

NON-AMMONIATED

DIRECTIONS

Mix stripper per instructions for heavy, normal, or light coating removal.
Apply solution liberally to the floor and allow to soak — do not allow to dry.
Scrub floor with automatic scrubber or stripping machine.
Rinse thoroughly with clean water and allow floor to dry before applying finish.

Read all directions and Safety Data Sheet (SDS) before using.
Directions and SDS are available for download at pioneereclipse.com

TECHNICAL DATA

Description Non-ammoniated, ultra high performance stripper

Appearance Clear

Viscosity (Brookfield) <20 centipoise
@ 68°F (20°C)

Flash Point >200°F (93°C)
ASTM D56-05 (2010)

VOC 60% (as supplied)
40 CFR PART 59 SUBPART C 2.8% (1:20)
1.90% (1:30)
1.43% (1:40)

Fragrance None added

Shelf Life 2 years
ASTM D1791-93 (2008)

Density 8.2 lb/gal @ 68°F
ASTM D1475 D-98 (2008) 0.98 kg/L @ 20°C



Product Code	549FS	549MP	549Q12
Volume	2.50 US gallons	1.06 US gallons	32 US ounces
Shipping Package	2 x 2.5 gallons	4 x 4 1.0 gallons	12 x 32 ounces
Pallet Quantity	48	48	44