



# Lumen L556™

## HEAVY DUTY FLOOR STRIPPER

An effective stripper for multiple coat removal.



SURFACES



### WHY LUMEN L556 HD FLOOR STRIPPER:

## FAST ACTING STRIPPER FOR ANY APPLICATION

25% actives content

## EFFECTIVE RESULTS EVEN AFTER NUMEROUS SCRUB AND RECOATS

### TECHNICAL DATA

**Description** Fast-acting floor stripper

**Appearance** Clear colorless

**Viscosity  
(Brookfield)** <10 centipoise  
@ 68°F (20°C)

**Flash Point** > 200 °F / > 93 °C  
ASTM D56-22

**VOC** 24.5% (as supplied)  
40 CFR PART 59 SUBPART C 4.8% (1:4)  
2.7% (1:8)

**Fragrance** None added

**Shelf Life** 2 years  
ASTM D1791-93

**Density** 8.3 lb/gal @ 68°F  
ASTM D1475 D-13 1.0 kg/L @ 20°C

### DIRECTIONS

Mix stripper per instructions for heavy or light coating removal.


Apply solution liberally to the floor and allow to soak — do not allow to dry.

Scrub floor with automatic scrubber or stripping machine.

Rinse thoroughly with clean water and allow floor to dry before applying finish.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)



<b>Product Code</b>	556FS	556FSC	556MPE
<b>Volume</b>	2.50 US gallons	2.50 US gallons	4 Liters
<b>Shipping Package</b>	2 x 2.5 gallons	2 x 2.5 gallons	4 x 4L
<b>Pallet Quantity</b>	48	48	48

556\_PDS 06/24