

WoodPrime™

WOOD FLOOR SEALER

A water-based sanding sealer to optimize adhesion and protect against tannin bleed.



WHY WOODPRIME:

STRONG BUILD LAYER

High solids (34%) formulation

MINIMIZES TANNIN BLEED & GRAIN RAISE

Acrylic, water-based polymer

QUICK DRY TIME

DIRECTIONS

Shake or stir well for 30 - 45 seconds. Apply 2 coats for wood floor coating. Allow 1 - 2 hours between coats.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

TECHNICAL DATA

Description	Acrylic wood floor sealer
Appearance	Milky white
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise
Coverage Rate	600-800 ft ² /gal
Dry Time	2-3 hours for first coat
VOC 40 CFR Part 59 Subpart C	<238 g/L
Non-Volatile Solids ASTM D2834-95 (2008)	34%
pH ASTM E70-07	8.0
Fragrance	Characteristic
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.8 lb/gal
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

Product Code	701FS
Volume	2.50 US gallons
Shipping Package	2 x 2.5 gallons
Pallet Quantity	48