

WoodStar™

WOOD FLOOR COATING



A single-component, water-based acrylic wood floor coating.

WHY WOODSTAR:

IDEAL FOR COMMERCIAL, RESIDENTIAL & SPORT FLOORS

Single-component, water-based formula

NO CHANGE IN COLOR OR APPEARANCE OF FLOOR

Clear and colorless

DURABLE

Internally cross-linked acrylic

DIRECTIONS

Apply 1 coat of sanding sealer. Allow to dry 2 - 3 hours. Lightly sand floor. Vacuum, dust mop, and tack the floor.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

TECHNICAL DATA

Description	Water-based acrylic coating
Appearance	Milky white
Available Sheens	Satin, Semi Gloss, High Gloss
pH ASTM E70-0	8.5
Specular Gloss (60°) ASTM D1455-87 (2008)	Satin: 20-25 Semi Gloss: 45-50 High Gloss: > 85
Viscosity (Brookfield) @ 68°F (20°C)	<50 centipoise
Coverage Rate	500-600 ft ² /gal
Dry Time	1-2 hours for first coat
VOC 40 CFR Part 59 Subpart C	<215 g/L
Non-Volatile Solids ASTM D2834-95 (2008)	31%
Fragrance	Characteristic
Slip Resistance ULTM410	Meets requirement
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.7 lb/gal
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

SURFACES

WOOD FLOORS

Product Code	702FS	702MPE
Volume	2.50 US gallons	4 liters
Shipping Package	2 x 2.5 gallons	4 x 4 liters
Pallet Quantity	48	48