



Concentrated cleaner for cold water extraction or spray-on application.

## DIRECTIONS

Read all directions and Safety Data Sheets (SDS) before using.

For synthetic carpet extraction:

1. Mix cleaner in a carpet extractor at a dilution of: 1:128 (1 US oz per gallon / 8 ml per 1 liter cold water).
2. Thoroughly clean with carpet extractor. Use defoamer in recovery tank if required.
3. Groom carpet with clean carpet rake or stiff synthetic broom and allow to dry.

As a pre-spray:

1. Thoroughly vacuum carpet and pre-treat spots.
2. Mix in a pump-up sprayer at a dilution of 1:8 (16 US oz per gallon / 125 ml per 1 liter of cold water).
3. Spray carpet completely. Agitate with a carpet rake, extractor brush, shampoo brush or bonnet.
4. Allow 10-15 minutes for cleaner to completely loosen soils. Do not allow to dry out.
5. Thoroughly clean with carpet extractor and water. Use defoamer in recovery tank if required.
6. OPTIONAL: Thoroughly rinse carpet with extractor and extraction rinse according to label directions.
7. Groom carpet and allow to dry.

## PRODUCT INFO

**Product Code** 831MPE

**Volume** 1.06 US gallons  
(3,8 liters)


**Shipping Package** 4 x 1.06 gallons  
(4 x 3,8 liters)

**Pallet Quantity** 48

## SURFACES



CARPET



UPHOLSTERY

## TECHNICAL DATA

<b>Description</b>	Carpet extraction & pre-spray cleaner
<b>Appearance</b>	Clear, light amber liquid
<b>pH</b> ASTM E70-07 (2015)	9.5 (as supplied)
<b>Viscosity (Brookfield)</b> @ 68°F/20°C	<10 centipoise
<b>VOC</b> 40 CFR Part 59 Subpart D	0.78% (as supplied) 0.09% (1:8) 0.01% (1:128)
<b>Fragrance</b>	None Added
<b>Shelf Life</b> ASTM D1791-93 (2015)	2 years
<b>Density</b> ASTM D1475-13	8.9 lb/gal @ 68°F 1.07 kg/L @ 20°C
<b>Flash Point</b> (ASTM D56-05) (2010)	>200°F (93°C)
<b>Freeze/Thaw</b> ASTM D3209-93 (2015)	Passes 3 cycles
<b>Container</b>	1.06 US gallons

