

Conforms to 1910.1200 Issued: Aug. 25, 2023 Supersedes: May 8, 2020

549

FORMULA X-TREME™

Product Number:

1: PRODUCT AND COMPANY IDENTIFICATION

<u>Product Name:</u> Formula X-TREME High Performance Stripper

Recommended Use: Non-ammoniated, low foaming floor stripper

Concentrate- dilute prior to use.

Product intended for commercial and industrial use only.

Uses Advised Against: Other than per labelled instructions

Manufacturer Address:

Amano Pioneer Eclipse Corporation

P.O. Box 909 1 Eclipse Road Sparta, NC 28675

Telephone: 1-336-372-8080 Email: sds@pioneereclipse.com Internet: www.pioneereclipse.com

FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure or Accident. Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada 1-703-527-3887 (collect calls accepted)

2: HAZARDS IDENTIFICATION

Classification: Acute Toxicity - Inhalation - Category 4

Acute Toxicity - Oral - Category 4
Eye Damage - Category 1
Skin Corrosion - Category 1B

Specific Target Organ Toxicity (Single Exposure) - Category 3

Signal Word: DANGER

Pictogram:





Hazard Statements:

Harmful if inhaled.

Harmful if swallowed.

Causes serious eye damage.

Causes severe skin burns and eye damage.

May cause respiratory irritation.

Precautionary Statements:

Do not breathe mist/vapors/spray.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/eye protection/face protection.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulation.

Immediately call a POISON CENTER/doctor if you feel unwell.

 $\label{eq:continuous} \text{IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor.}$

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Other Hazards: None known

Supplemental Information: None known



Conforms to 1910.1200 Issued: Aug. 25, 2023 Supersedes: May 8, 2020

FORMULA X-TREME™

3: COMPOSITION/INFORMATION ON INGREDIENTS				
Ingredient	CAS Number	Weight % *		
ethylene glycol monobutyl ether	111-76-2	30 - 45		
benzyl alcohol	100-51-6	20 - 30		
monoethanolamine	141-43-5	15 - 25		

^{*} Exact concentration of the ingredients has been withheld as a trade secret.

4: FIRST AID MEASURES

DECRIPTION OF FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eye with plenty of water for at least 15 minutes. (If easy to do, remove

contact lenses, if worn). Seek medical attention.

Skin Contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing

contaminated clothing and shoes. Seek medical attention.

Inhalation: If breathing is difficult. Remove subject to fresh air. Seek medical attention immediately.

Ingestion: Call a physician or poison control center. Do not induce vomiting. Seek medical advice immediately.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye Contact: Causes eye damage. Skin Contact: Causes skin burns.

Inhalation: Harmful if inhaled. May cause respiratory tract irritation.

Ingestion: Harmful if swallowed. May cause burns to mouth, throat and stomach.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Treat symptomatically.

5: FIRE-FIGHTING MEASURES

Suitable Extinguishing media: Water spray, CO₂ dry chemical, alcohol-type or universal type foams

<u>Specific Hazards:</u> Corrosive liquid. (See Sections 8 and 10.) Do not spray a solid stream of water or foam

directly in hot liquid. This may cause frothing.

<u>Protective Equipment and Precautions:</u> Fire fighters should wear NIOSH approved breathing apparatus. Materials

can splatter above 100° C / 212° F

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Put on personal protective equipment (see Section 8). Keep spectators away.

Floors may be slippery: use care to avoid falling.

Environment Precautions: Keep spills and cleaning run-off out of sewers and open bodies of water.

CONTAINMENT AND CLEAN-UP

Small Spills: Absorb spill with inert material (e.g. sand, earth) and dispose of as waste material in accordance with local, state

and federal regulations.

Large Spills: Dike and contain spill with inert material (e.g. sand, earth). Neutralize pill area. Transfer liquid to containers for

recovery or disposal and solid diking material to separate containers for disposal.

Waste Disposal: Dispose of contaminated solids and diking material, in accordance with local, state and federal

regulations. Non-salvageable liquid should be drummed and disposed of in accordance with local,

state and federal regulations.

7: HANDLING AND STORAGE

<u>Precautions for Safe Handling:</u> Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only in

well-ventilated areas. Avoid breathing vapors or mists. Remove and wash contaminated

clothing and footwear before re-use.

Conditions for Safe Storage: Storage temperature (Max. 60°C/140°F - Min. 1°C/34°F)

Other Information: Keep from freezing. Keep container sealed when not in use. Keep out of reach of

children.



Conforms to 1910.1200 Issued: Aug. 25, 2023 Supersedes: May 8, 2020

FORMULA X-TREME™

8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

Ingredient	CAS Number	ACGIH		OSHA	
ingredient	CAS Number	TWA	STEL	TWA	STEL
ethylene glycol monobutyl ether	111-76-2	20 ppm (BEI)	-	50 ppm (skin)	ı
monoethanolamine	141-43-5	3 ppm	6 ppm	3 ppm	-

Engineering Controls:

Use only with adequate ventilation. Use local ventilation and other engineering controls to maintain airborne contaminants below established and recommended exposure limits. If this product contains ingredients with exposure limits, monitoring may be required to determine the effectiveness of ventilation and other control measures.

Personal Protective Equipment (PPE)

Eye/Face Protection: Wear eye protection/face protection. **Skin Protection:** Wear chemical resistant gloves.

Respiratory Protection: Respiratory protection should be worn when there is a potential of inadequate ventilation. If

exposure limits are exceeded or symptoms are experienced, use an approved respirator.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety practice.

9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: clear liquid

Odor: butyl odor (no added fragrance)

Odor Threshold: data not available

pH: 12.5

Freezing Point: data not available Boiling Point: data not available

Flash Point: >200°F />93°C (ASTM D56)

Evaporation Rate: less than water

Flammability (solid/gas): not applicable to liquids
Flammability limits: data not available
Vapor Pressure: data not available
Vapor Density: data not available

Relative Density: 8.2 lb/gal @ 68°F / 0.98 kg/l @ 20°C

Solubility: miscible in water
Partition Coefficient: data not available
Auto Ignition temperature: data not available
Decomposition Temperature: data not available
Viscosity: < 20 centipoise @ 68°F

VOC: 61.5%(as supplied), 2.9%(1:20), 2.6 (1:23), 2.0%(1:30), 1.5%(1:40)

10: STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions. Reacts exothermically with acids: release of heat.

Stability: Stable under normal conditions.

Hazardous reactions: None under normal conditions. Reacts exothermically with acids: release of heat.

Conditions to avoid: None known.

<u>Incompatible materials:</u> Strong acids and oxidizing agents. Do not mix with other chemicals unless stated on the product

label.

Hazardous decomposition products: carbon monoxide, carbon dioxide and nitrogen oxides

11: TOXICOLOGICAL INFORMATION

Acute Toxicity: Toxicity testing has not been completed on the mixture.

ATE mix (oral) 1390 mg/kg Harmful if swallowed.

ATE $_{mix}$ (dermal) > 2000 mg/kg

ATE _{mix} (inhalation) 18 mg/l (vapor) Harmful if inhaled. May cause respiratory irritation.



Conforms to 1910.1200 Issued: Aug. 25, 2023 Supersedes: May 8, 2020

FORMULA X-TREME™

LOCAL EFFECTS

Skin contact: Causes severe skin burns. **Eye contact:** Causes serious eye damage.

Sensitization: None expected Chronic effects: None expected

SPECIFIC EFFECTS

Carcinogenicity:None knownReproductive effects:None knownTeratogenicity:None knownMutagenicity:None known

COMPONENT INFORMATION

Component	LD50 Oral- Rat (mg/kg)	LD50 Dermal - Rabbit (mg/kg)	LC50 Inhalation- (mg/l)
ethylene glycol monobutyl ether	1200	>2000	guinea pig (1hr), >3.1
benzyl alcohol	1230	2000	rat (8hr), 8.9
monoethanolamine	1515	2504	rat (4hr), > 1.3

Carcinogenicity:

Component	IARC	NTP	OSHA
ethylene glycol monobutyl ether	IARC 3	Not listed	Not listed

12: ECOLOGICAL INFORMATION

Ecotoxicity: Ecological testing has not been completed on the mixture.

Persistence and Degradability:Data not available.Bioaccumulative Potential:Data not available.Mobility in Soil:Data not available.Other Adverse Effects:Data not available.

13: DISPOSAL CONSIDERATIONS

Waste residues or unused products:

Disposal of this material should be in accordance with local, regional and national regulations.

This product, as sold, if discarded or disposed, is a hazardous waste according to 40 CFR 261.

It is the responsibility of the end user to determine, at the time of disposal, if the waste solution meets the criteria for hazardous waste.

RCRA Hazard Class (as sold): D002 - Corrosive

14: TRANSPORT INFORMATION

UN Number: UN1760

UN Proper Shipping Name: Corrosive liquid, n.o.s. (ethanolamine)

Hazard Class:8Packing Group:IIMarine Pollutant:NoneTransport in Bulk:N/A

Other Information: Package Volumes < 1L are shipped under Limited Quantity Exemption.

15: REGULATORY INFORMATION

U.S. REGULATIONS/REPORTING:

Ingredient	CAS Number	SARA 302/304	SARA 313	CERCLA
ethylene glycol monobutyl ether	111-76-2	N/L	1.00%	N/L



Conforms to 1910.1200 Issued: Aug. 25, 2023 Supersedes: May 8, 2020

FORMULA X-TREME™

STATE RIGHT-TO-KNOW STATUS:

Ingredient	CAS Number	MA - RTK	NJ - RTK	PA - RTK	RI - RTK
ethylene glycol monobutyl ether	111-76-2	present	present	present	present
benzyl alcohol	100-51-6	present	N/L	present	N/L
monoethanolamine	141-43-5	present	present	present	present

CALIFORNIA PROPOSITION 65:

Components are not present on CA Prop 65 listing.

CANADA REGULATIONS/REPORTING:

This product has been classified in accordance with the hazard criteria of the Hazardous Product Regulation (HPR) and the SDS contains the information required by the HPR.

NPRI Substance List

Ingredient	CAS Number	Part #	Reporting Threshold
Butoxyethanol	111-76-2	Part 1A	10 tonnes MPO
Butoxyetilarioi	111-70-2	Part 5	1 tonne air release

2-Butoxyethanol Regulations

Product diluted per label directions complies to 2-Butoxyethanol Regulation requirements.

Product Category	Dilution Ratio	Concentration Limit
Floor or Baseboard stripper	1:23	≤ 2 % (w/w)

16: OTHER INFORMATION

Abbreviations Used:

N/A - Not applicable


N/E - Not Established

N/L - Not Listed

IARC 3 - Unclassifiable as to carcinogenicity in humans.

Revision Information:

Aug. 25, 2023 - Revisions § 1, 3, 4, 6, 8, 9, 10, 11, 13 & 15



Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) or the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnish of such information.

This SDS has been provided to you in accordance with the OSHA Hazard Communication Standard (29CFR1910.1200).

IMPORTANT SAFETY INFORMATIONDO NOT DISCARD**PLEASE ROUTE TO COMPANY SAFETY OFFICER**