

Product Number:

Conforms to 1910.1200 Issued: May 28, 2024 Supersedes: Feb. 1, 2024

LUMEN L556™

556

1: PRODUCT AND COMPANY IDENTIFICATION

<u>Product Name:</u> Lumen L556 Heavy Duty Floor Stripper

Recommended Use: Non-ammoniated, heavy duty floor stripper

Concentrate- dilute prior to use.

Product intended for commercial and industrial use only.

Uses Advised Against: Other than per labelled instructions

Manufacturer Address:

Amano Pioneer Eclipse Corporation

P.O. Box 909 1 Eclipse Road Sparta, NC 28675

Telephone: 1-336-372-8080 Email: sds@pioneereclipse.com Internet: www.pioneereclipse.com

FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure or Accident. Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada 1-703-527-3887 (collect calls accepted)

2: HAZARDS IDENTIFICATION

Classification: Skin Corrosion- Category 1B

Eye Damage - Category 1

Specific Target Organ Toxicity (Single Exposure) - Category 3

Signal Word: DANGER

Pictogram:





Hazard Statements:

Causes severe skin burns and eye damage.

Cause serious eye damage.

May cause respiratory irritation.

Precautionary Statements:

Do not breathe mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wash thoroughly after handling.

Wear protective gloves and eye protection/face protection.

Wash contaminated clothing before reuse.

Store locked up.

Store in a well ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Immediately call a POISON CENTER/doctor if you feel unwell.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Other Hazards: None known

Supplemental Information: None known



Conforms to 1910.1200 Issued: May 28, 2024 Supersedes: Feb. 1, 2024

LUMEN L556™

3: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Weight % *
ethylene glycol monobutyl ether	111-76-2	10 - 30
monoethanolamine	141-43-5	5 - 10

^{*} Exact concentration of the ingredients has been withheld as a trade secret.

4: FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eye with plenty of water for at least 15 minutes. (If easy to do, remove

contact lenses, if worn). Seek medical attention.

Skin Contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing

contaminated clothing and shoes. Seek medical attention.

Inhalation: If breathing is difficult. Remove subject to fresh air. Seek medical attention immediately.

Ingestion: Call a physician or poison control center. Do not induce vomiting. Seek medical advice immediately.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye Contact: Causes eye burns. **Skin Contact:** Causes skin burns.

Inhalation: May cause respiratory irritation. May cause corrosive effects to nose, throat and respiratory tract.

Ingestion: May cause burns and irritation to mouth, throat and stomach.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Treat symptomatically.

5: FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing media:</u> Water spray, CO_{2,} dry chemical, alcohol-type or universal type foams

Specific Hazards: Corrosive liquid. (See Sections 8 and 10.) Do not spray a solid stream of water or foam

directly in hot liquid. This may cause frothing.

Protective Equipment and Precautions: Fire fighters should wear NIOSH approved breathing apparatus. Materials

can splatter above 100° C / 212° F

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Put on personal protective equipment (see Section 8). Keep spectators away. Floors

may be slippery: use care to avoid falling.

Environment Precautions: Keep spills and cleaning run-off out of sewers and open bodies of water.

CONTAINMENT AND CLEAN-UP

Small Spills: Absorb spill with inert material (e.g. sand, earth) and dispose of as waste material in accordance

with local, state and federal regulations.

Large Spills:

Dike and contain spill with inert material (e.g. sand, earth). Neutralize spill area. Transfer liquid to

containers for recovery or disposal and solid diking material to separate containers for disposal.

Waste Disposal: Landfill or incinerate the contaminated solids and diking material in accordance with local, state and

federal regulations. Non-salvageable liquid should be drummed and disposed of in accordance with

local, state and federal regulations.

7: HANDLING AND STORAGE

<u>Precautions for Safe Handling:</u> Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only

in well-ventilated areas. Avoid breathing vapors or mists. Remove and wash

contaminated clothing and footwear before re-use.

Conditions for Safe Storage: Storage temperature (Max. 60°C/140°F - Min. 1°C/34°F)

Other Information: Keep from freezing. Keep container sealed when not in use. Keep out of reach of

children.



Conforms to 1910.1200 Issued: May 28, 2024 Supersedes: Feb. 1, 2024

LUMEN L556™

8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

		ACGIH		OSHA	
Ingredient	CAS Number	TWA	STEL	TWA	STEL
ethylene glycol monobutyl ether	111-76-2	20 ppm (BEI)	N/L	50 ppm (skin)	N/L
monoethanolamine	141-43-5	3 ppm	6 ppm	3 ppm	N/L

Engineering Controls: Use only with adequate ventilation. Use local ventilation and other engineering controls to maintain

airborne contaminants below established and recommended exposure limits. If this product contains ingredients with exposure limits, monitoring may be required to determine the effectiveness

of ventilation and other control measures.

Personal Protective Equipment (PPE)

Eye/Face Protection: Wear eye protection

Skin Protection: Wear chemical resistant gloves.

Respiratory Protection: Respiratory protection should be worn when there is a potential of inadequate ventilation. If

exposure limits are exceeded or symptoms are experienced, use an approved respirator.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety practice.

9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: clear colorless, liquid

Odor: no added fragrance, characteristic

Odor Threshold: data not available

pH: 11.4

Freezing Point: data not available
Boiling Point: data not available

Flash Point: > 200°F / > 93°C (ASTM D56)

Evaporation Rate: less than water

Flammability (solid, gas):

Flammability limits:

Vapor Pressure:

Vapor Density:

not applicable to liquids
data not available
data not available
data not available

Relative Density: 8.3 lb/gal @ 68°F / 1.0 kg/L @ 20°C

Solubility: miscible in water
Partition Coefficient: data not available
Auto Ignition temperature: data not available
Decomposition Temperature: data not available
Viscosity: < 10 cps @ 68°F

VOC: 24.53% (as supplied), 2.68% (1:8), 2.19% (1:10)

10: STABILITY AND REACTIVITY

Reactivity: None expected under normal conditions.

Reacts exothermically with acids: release of heat.

<u>Stability:</u> Stable under normal conditions. **Hazardous reactions:** None known under normal conditions.

Reacts exothermically with acids: release of heat.

<u>Conditions to avoid:</u> Improper order of dilution.

Incompatible materials: Strong acids and oxidizing agents.

Do not mix with other chemicals unless stated on the product label.

Hazardous decomposition products: carbon oxides, nitrogen oxides

11: TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: Toxicity testing has not been completed on the mixture.

Based on available data, the classification criteria are not met.



Conforms to 1910.1200 Issued: May 28, 2024 Supersedes: Feb. 1, 2024

LUMEN L556™

ATE $_{mix}$ (oral): > 2000 mg/kg ATE $_{mix}$ (dermal): > 2000 mg/kg

ATE $_{mix}$ (inhalation): > 20 mg/l (4 hr/vapor)

LOCAL EFFECTS

Skin contact:Can cause severe skin burns.Eye contact:Can cause serious eye damage.Inhalation:May cause respiratory irritation.

Sensitization: None expected
Chronic effects: None expected

SPECIFIC EFFECTS

Carcinogenicity:None knownReproductive effects:None knownTeratogenicity:None knownMutagenicity:None known

COMPONENT INFORMATION

Component	LD50 Oral- Rat (mg/kg)	LD50 Dermal - Rabbit (mg/kg)	LC50 Inhalation- Rat (mg/l)
ethylene glycol monobutyl ether	470	220	2.21 (4hr)
monoethanolamine	1720	1025	N/A

Carcinogenicity:

Component	IARC	NTP	OSHA
ethylene glycol monobutyl ether	IARC 3	N/L	N/L

12: ECOLOGICAL INFORMATION

Ecotoxicity: Ecological testing has not been completed on the mixture.

Persistence and Degradability:Data not available.Bioaccumulative Potential:Data not available.Mobility in Soil:Data not available.Other Adverse Effects:Data not available.

13: DISPOSAL CONSIDERATIONS

It is the responsibility of the end user to determine, at the time of disposal, if the waste solution meets the criteria for hazardous waste.

Disposal of this material should be in accordance with local, regional and national regulations.

Packaging: Do not reuse empty containers.

14: TRANSPORT INFORMATION

UN Number: UN1760

<u>UN Proper Shipping Name:</u> Corrosive liquid, n.o.s. (ethanolamine)

Hazard Class:8Packing Group:IIIMarine Pollutant:NoneTransport in Bulk:N/A

<u>Other Information:</u> Package Volumes < 5L are shipped under Limited Quantity Exemption.

15: REGULATORY INFORMATION

U.S. REGULATIONS/REPORTING:

Ingredient	CAS Number	SARA 302/304	SARA 313 Reporting Threshold	CERCLA
ethylene glycol monobutyl ether	111-76-2	not listed	1.0%	N230, &



Conforms to 1910.1200 Issued: May 28, 2024 Supersedes: Feb. 1, 2024

LUMEN L556™

STATE RIGHT-TO-KNOW STATUS:

Ingredient	CAS Number	MA - RTK	NJ - RTK	PA - RTK	RI - RTK
ethylene glycol monobutyl ether	111-76-2	present	present	present	present
monoethanolamine	141-43-5	present	present	present	present

CALIFORNIA PROPOSITION 65:

Components are not present on CA Prop 65 listing.

CANADA REGULATIONS/REPORTING:

SOR/2015-17: Hazardous Product Regulations

This product has been classified in accordance with the hazard criteria of the Hazardous Product Regulation (HPR) and the SDS contains information required by the HPR.

SOR/2006-347: 2-Butoxyethanol Regulations

Product diluted per label directions complies with 2-Butoxyethanol Regulations.

Product Category	Dilution Ratio	Concentration Limit
Floor or Baseboard stripper	1:10	≤ 2 % (w/w)

16: OTHER INFORMATION

Abbreviations Used:

& CERCLA hazardous substance, no RQ is assigned to this generic class

ATE mix Acute Toxicity Estimate - mixture
CAS Chemical Abstract Service Number

CERCLA Comprehensive Environmental Response, Compensation and Liability Act

IARC International Agency for Research on Cancer IARC 3 Unclassifiable as to carcinogenicity in humans.

LC50 Median Lethal Concentration

LD50 Median Lethal Dose

N230 Glycol ethers, generic class NTP National Toxicology Program

OSHA Occupational Safety and Health Administration
RCRA Resource Conservation and Recovery Act
SARA Superfund Amendments and Reauthorization Act

SDS Safety Data Sheet

VOC Volatile Organic Compound

Revision Information:

May 28, 2024 - Revision § 1



Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) or the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnish of such information.

This SDS has been provided to you in accordance with the OSHA Hazard Communication Standard (29CFR1910.1200).

IMPORTANT SAFETY INFORMATIONDO NOT DISCARD**PLEASE ROUTE TO COMPANY SAFETY OFFICER**