



EnviroStar Green Floor Sealer is an environmentally preferred sealer that provides a durable foundation for EnviroStar Green floor coatings.

DIRECTIONS

Read all directions and Safety Data Sheets (SDS) before using.

1. Strip and properly neutralize the floor, allowing it to dry thoroughly.
2. Apply 2 thin coats of sealer using a clean synthetic mop. Allow floor to dry thoroughly between coats.
3. Apply recommended floor coating, following manufacturer's instructions.

PRODUCT INFO

Product Code	413FS	413MPE
Volume	2.50 US gallons	4 liters
Shipping Package	2 x 2.5 gallons	4 x 4 liters
Pallet Quantity	48	48

SURFACES



TECHNICAL DATA

Description	Water based floor sealer
Appearance	Milky white
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise
Coverage Rate	2000 to 2500 ft ² /gal 49 to 61 m ² /liter
Dry Time	About 30 minutes
Removability ASTM D1792-06	Excellent
VOC 40 CFR Part 59 Subpart C	0.94%
Non-Volatile Solids ASTM D2834-95 (2008)	22%
pH ASTM E70-07	7.6
Fragrance	Non ammoniated
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles
Container	2.5 US gal/9.5 L (FS packaging) 1.06 US gal/4 L (MPE packaging)

CARB compliant



RECOGNIZED FOR SAFER CHEMISTRY
WWW.EPA.GOV/DFE