



Solstice is an excellent “dri-bright” floor finish with outstanding resistance to scuffs, scratches, black heel marks and detergent scrubbing. Low maintenance and long lasting characteristics reduces costs and stripping operations.

DIRECTIONS


Read all directions and Safety Data Sheets (SDS) before using.

1. For a floor that has been stripped, properly neutralized, rinsed and allowed to dry thoroughly, apply 5-6 thin coats using a clean synthetic mop. Allow the floor to dry thoroughly between coats and prior to burnishing.
2. Optional: Apply 2 thin coats of floor sealer for old or porous floors or for high traffic areas, then apply 4 coats of finish.
3. For a floor that has been deep scrubbed and allowed to dry thoroughly, apply 1-2 thin coats using a clean synthetic mop. Allow floor to dry thoroughly between coats and prior to burnishing.

PRODUCT INFO

Product Code	140FS	140FSE	140MPE
Volume	2.50 US gallons	10 liters	4 liters
Shipping Package	2 x 2.5 gallons	2 x 10 liters	4 x 4 liters
Pallet Quantity	48	48	48

SURFACES



VCT LINOLEUM MARMOLEUM

TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white
Specular Gloss (60°) ASTM D1455-87 (2008)	>85
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise
Coverage Rate	2500 to 3000 ft ² /gal 61 to 74 m ² /liter
Dry Time	30 minutes
Removability ASTM D1792-06	Excellent
VOC 40 CFR Part 59 Subpart C	0.03%
Non-Volatile Solids ASTM D2834-95 (2008)	20%
Fragrance	Faintly acetic (non-ammoniated)
Slip Resistance ULTM410	Meets requirements
Shelf Life ASTM D1791-93 (2008)	1 year
Density ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.01 kg/L @ 20°C
Detergent Resistance ASTM D3207-92 (2008)	Excellent
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles
Container	2.5 US gal/9.5 L (FS packaging) 2.64 US gal/10 L (FSE packaging) 1.06 US gal/4 L (MPE packaging)



Floor Coating and Finishing materials as to slip resistance only. 42E6