



# Formula X™ UHP

ULTRA HIGH PERFORMANCE STRIPPER



Fast acting **Formula X Ultra High Performance Stripper** is a powerful, non-ammoniated formula that cuts through heavy build-up and hard to remove water-based sealers in record time.

## DIRECTIONS

Read all directions and Safety Data Sheet (SDS) before using.

- Mix stripper per the following dilutions:  
For sealer & coating removal:  
1:4 (250 ml per 1 liter of water).  
For coating removal only:  
1:8 (125 ml per 1 liter of water).
- Apply solution liberally to the floor and allow to soak for 10 minutes ensuring the solution does not dry.
- Scrub floor with automatic scrubber or stripping machine. Pick up dirty solution with automatic scrubber or wet vac.
- Rinse thoroughly with clean water or use EnviroStar Green All Purpose Neutralizer per label instructions. Allow floor to dry thoroughly.

Note: Test surface for color fastness in an inconspicuous area.

## PRODUCT INFO

**Product Code** 503L5

**Volume** 5 liters

**Shipping Package** 2 x 5 liters

**Pallet Quantity** 64 cases

## SURFACES

All resilient tile flooring ("VCT), and most types of terrazzo, marble and quarry tile.

Not recommended for asphalt, rubber or asbestos tile flooring.



## TECHNICAL DATA

<b>Description</b>	Non-ammoniated, ultra high performance stripper
<b>Appearance</b>	Clear liquid
<b>Fragrance</b>	No added fragrance
<b>Flash Point</b> <small>(ASTM D1792-06)</small>	<93°C
<b>Viscosity (Brookfield)</b> <small>@ 68°F (20°C)</small>	<10 mPa.s
<b>Shelf Life</b> <small>ASTM D1791-93 (2008)</small>	2 years
<b>Density</b> <small>ASTM D1475-13 (2008)</small>	+/- 0.99 g/cm <sup>3</sup>
<b>Freeze/Thaw</b> <small>ASTM D3209-93 (2008)</small>	Passes 3 cycles ASTM D3209-93 (1998)
<b>VOC</b> <small>40 CFR Part 59 Subpart D</small>	+/- 42%

SDS available for download at [www.pioneereclipse.com](http://www.pioneereclipse.com)

