



EnviroStar Non-Acid Washroom Cleaner is a powerful, ultra high performance, non-acid formula cleaner for all washroom surfaces.

DIRECTIONS

Read all directions and Safety Data Sheets (SDS) before using.

DTC: Product to be used only with the AquapHyll™ dilution control system. For recommended DTC 1:32 dilution rate use AquapHyll Portable Plus™ and wall mount dispensers in bottle setting.

DILUTION Mix cleaner at a dilution rate of 1:16 (8 oz per gal or 62 ml per 1 liter of cold water).

WASHROOMS Apply to surfaces and wipe clean.

TOILETS

1. If severely stained, remove as much water as possible.
2. Pour generously into bowl and on to swab.
3. Thoroughly clean all interior surfaces of the bowl including under the rim.
4. Rinse and flush.


URINALS

1. Wet swab and apply cleaner liberally to the inside of the urinal, concentrating under flush rim.
2. Rinse thoroughly and flush.

PRODUCT INFO

| Product Code | 334D | 334DTC | 334MPE |
|------------------|------------------|------------------|--------------|
| Volume | 1.06 US gallons | 0.53 US gallons | 4 liters |
| Shipping Package | 4 x 1.06 gallons | 4 x 0.53 gallons | 4 x 4 liters |
| Pallet Quantity | 48 | 88 | 48 |

SURFACES



TILE ALL WASHABLE SURFACES

TECHNICAL DATA

| | |
|--|---|
| Description | Washroom cleaner |
| Appearance | Clear colorless liquid |
| pH ASTM E70-07 | 10.5 (as supplied) |
| Viscosity (Brookfield) @ 68°F (20°C) | <10 centipoise |
| Fragrance | None added |
| Freeze/Thaw | Passes 3 cycles |
| Shelf Life ASTM D1791-93 (2008) | 2 years |
| Flash Point ASTM D56-05 (2010) | >200°F (>93°C) |
| Density ASTM D1475-98 (2008) | 8.7 lb/gal @ 68°F 1.04 kg/L @ 20°C DTC: 8.9 lb/gal @ 68°F DTC: 1.07 kg/L @ 20°C |
| VOC 40 CFR Part 59 Subpart C | 0.01% (as supplied) < 0.01% (1:16) DTC: 0.01% (as supplied) DTC: < 0.01% (1:32) |
| Container | 1.06 US gal/4 L (D packaging) 0.53 US gal/2 L (DTC packaging) 1.06 US gal/4 L (MPE packaging) |