



FloorMatte Non-Glare is an advanced floor coating specifically designed to provide a highly durable satin coating, without glare, for use in hospitals and long-term care facilities.

DIRECTIONS

Read all directions and Safety Data Sheet (SDS) before using.

1. For a floor that has been stripped, properly neutralized, rinsed and allowed to dry thoroughly, apply 2-3 thin coats of floor finish using a clean synthetic mop. Allow the floor to dry thoroughly between coats.
2. For a floor that has been deep scrubbed and allowed to dry thoroughly, apply 1-2 thin coats of floor finish using a clean synthetic mop. Allow floor to dry thoroughly between coats.

PRODUCT INFO

Product Code 114L5

Volume 5 liters

Shipping Package 2 x 5 liters

Pallet Quantity 64 cases

SURFACES



VCT



TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white liquid
Specular Gloss (60°) <small>ASTM D1455-87 (2008)</small>	<35
Viscosity (Brookfield)	<10 centipoise
Coverage Rate	61 to 74 m ² /liter
Dry Time	about 30 minutes
Removability <small>(ASTM D1792-06)</small>	Good
VOC <small>40 CFR Part 59 Subpart D</small>	5,22%
Non-volatile solids <small>ASTM D2834-95 (2008)</small>	16%
Fragrance	Pleasant
Slip Resistance <small>ASTM D2047-11</small>	Meets requirements
Shelf Life <small>ASTM D1791-93 (2008)</small>	1 year
Density <small>ASTM D1475-13 (2008)</small>	1,02 kg/liter
Detergent Resistance <small>ASTM D3207-92 (2008)</small>	Excellent
Freeze/Thaw <small>ASTM D3209-93 (2008)</small>	Passes 3 cycles