



Sta-Brite20 is an excellent, low maintenance coating with outstanding resistance to scuffs, scratches, black heel marks and detergent scrubbing.

DIRECTIONS

Read all directions and Safety Data Sheet (SDS) before using.

- For a floor that has been stripped, properly neutralized, rinsed and allowed to dry thoroughly, apply 3-6 thin coats of floor finish using a clean synthetic mop. Allow the floor to dry thoroughly between coats.
Optional: Apply 2 thin coats of floor sealer for old or porous floors or for high traffic areas, then apply 2-4 coats of finish.
- For a floor that has been deep scrubbed and allowed to dry thoroughly, apply 1-2 thin coats of floor finish using a clean synthetic mop. Allow floor to dry thoroughly between coats.

PRODUCT INFO

Product Code 130L5

Volume 5 liters

Shipping Package 2 x 5 liters

Pallet Quantity 64 cases

SURFACES



VCT



TECHNICAL DATA

Description	Polymer emulsion
Appearance	Milky white opaque liquid
Specular Gloss (60°) <small>ASTM D1455-87 (2008)</small>	>85
Viscosity	< 10mPa.s (dynamic)
Coverage Rate	61 to 74 m ² /liter
Dry Time	about 30 minutes
Removability <small>(ASTM D1792-06)</small>	Excellent
VOC	5,61%
Non-volatile solids <small>ASTM D2834-95 (2008)</small>	20%
Fragrance	Slight ammonia
Slip Resistance <small>ASTM D2047-11</small>	Meets requirements
Shelf Life <small>ASTM D1791-93 (2008)</small>	1 year
Density <small>ASTM D1475-13 (2008)</small>	1,02 kg/liter
Detergent Resistance <small>ASTM D3207-92 (2008)</small>	Excellent
Freeze/Thaw <small>ASTM D3209-93 (2008)</small>	Passes 3 cycles